

SunESS Power All-in-One

Battery Module						
Battery Type	LiFePO4					
Nominal energy	5kWh					
Usable energy	4.5kWh					
Rated voltage	400V					
Voltage range	350~450V					
Rated charge/discharge power	2.5kW					
Peak output power	4.2kW/20s					
Weight	52kg					
Dimensions (W/H/D)	653/315/189mm					
Inverter Module	SW5KH3UT	SW6KH3UT	SW8KH3UT	SW10KH3UT	SW12KH3UT	SW15KH3UT
PV Input Parameters						
Max. input power	8000W	9000W	12000W	15000W	22500W	22500W
Max. input voltage	1000V					
MPPT voltage range	180~850V					
Start-up voltage	180V					
Max. input current per MPPT*	A: 15A	A: 15A	A: 15A / B: 30A	A: 15A / B: 30A	A: 15A / B: 30A	A: 15A/ B: 30A
Max. short-circuit current per MPPT*	A: 19A	A: 19A	A: 19A / B: 38A	A: 19A / B: 38A	A: 19A / B: 38A	A: 19A/ B: 38A
Number of MPPTs	1	1	2	2	2	2
Number of input strings per MPPT*	A: 1	A: 1	A: 1/ B: 2	A: 1/ B: 2	A: 1/ B: 2	A: 1/ B: 2
Battery Input Parameters						
Support battery capacity	5~40kWh					
Rated battery voltage	400V					
Battery voltage range	350~450V					
Max. continuous charging current	23A			46A		
Max. continuous discharge current	23A			46A		
Max. discharge power	5000W	6000W	8000W	10000W	12000W	15000W
Max. charging power	5000W	6000W	8000W	10000W	12000W	15000W
Output parameters(On-grid)						
Rated output power	5000W	6000W	8000W	10000W	12000W	15000W
Max. output apparent power	5000VA	6000VA	8000VA	10000VA	12000VA	15000VA
Max. input apparent power	8000VA	9000VA	12000VA	15000VA	18000VA	22500VA
Rated output voltage	220/380V 230/400V 3W/N/PE					
Rated output frequency	50Hz					
Max. output current	8.4A	10A	13.4A	16.7A	20A	25A
Max. input current	12.2A	13.7A	18.2A	22.8A	27.4A	34.2A
Power factor	0.8 leading to 0.8 lagging					
THDi	<3%					
Output parameters(Off-grid)						
Off-grid rated apparent power	5000VA	6000VA	8000VA	10000VA	12000VA	15000VA
Max. output apparent power	5500VA	6600VA	8800VA	11000VA	13200VA	16500VA
Max. output current	7.6A	10A	13.4A	16.7A	20A	25A
Rated output voltage	220/380V 230/400V 3W/N/PE					
Rated output frequency	50Hz					
THDv (@Linear Load)	<3%					
Efficiency						
Max. efficiency	97.4%	97.4%	97.8%	97.8%	97.8%	97.8%
Euro. Efficiency	96.5%	96.5%	96.8%	96.8%	97%	97%
Protection						
Input DC switch	Integrated					
Insulation Resistance Detection	Integrated					
Residual current monitoring	Integrated					
Input reverse polarity protection	Yes					
Anti-Islanding Protection	Yes					
Over current protection	Yes					
AC short circuit protection	Yes					
AC Over voltage protection	Yes					
AFCI(Arc Fault Circuit Interrupter) Protection	Optional					
Dry contact remote scheduling	Yes					
DC Surge Protection	Type II	Type II	Type II	Type II	Type II	Type II
AC surge protection	Type II	Type II	Type II	Type II	Type II	Type II
Basic parameters						
Display	LED&APP					
BMS communication method	CAN					
Meter communication method	RS485					
Monitoring method	WiFi/bluetooth					
Topology	Transformerless					
Operating temperature range	- 30~60 °C (>45°Cderating)					
Weight	41kg					
Dimensions (W/H/D)	650/480/250mm					

**A" corresponds to the silkscreen marking "PV2" on the inverter. "B" corresponds to the silkscreen marking "PV1" on the inverter.